


T52

Series Manual Trolleys

1/2 to 20 metric tonne capacity, industrial quality, built for long life

Whether plain or geared, there's a trolley to fit every KITO hoist. The reliability, smoothness of operation, and safety of your hoist is dependent on the trolley. Be sure to choose KITO quality and safety for both the hoist and trolley.



FEATURES

- » 1/2 to 20 tonne capacity allows you to choose the capacity that meets your needs
- » At rated capacity, load-bearing parts are only stressed to 20% of their limit
- » Heat treated steel wheels are hardened for long, trouble-free life
- » Lifetime lubricated ball bearings increase reliability and reduce maintenance
- » Adjustable to fit any beam—tapered or flat flanged, easily adapted for your shop or plant
- » Low minimum radius for curved beams for smooth travel around tight curves
- » Safety Lugs as standard

SPECIFICATIONS

Capacity (tonne)	Model	Min. Radius for Curve (mm)	Standard Flange (mm)			Standard Flange (in)			Standard Drop (ft)	Ship Weight (lbs)
			Standard	W20 Extension	W30 Extension	Standard	W20 Extension	W30 Extension		
Plain Trolley - with Safety Lugs										
1/2	TSP2005	1100	50 - 102	103 - 203	204 - 305	2 - 4"	4 - 8"	8 - 12"	----	10
1	TSP2010	1300	58 - 127	128 - 203	204 - 305	2.25 - 5"	5 - 8"	8 - 12"	----	18
2	TSP2020	1500	82 - 153	----	154 - 305	3.25 - 6"	----	6 - 12"	----	31
3	TSP2030	1700	82 - 153	----	154 - 305	3.25 - 6"	----	6 - 12"	----	51
5	TSP2050	2300	100 - 178	----	179 - 305	4 - 7"	----	7 - 12"	----	116
10	TSP2100	3000	150 - 220	----	221 - 305	6 - 8.5"	----	8.5 - 12"	----	220
Geared Trolley - with Safety Lugs										
1	TSG2010	1300	58 - 127	128 - 203	204 - 305	2.25 - 5"	5 - 8"	8 - 12"	8	27
2	TSG2020	1500	82 - 153	----	154 - 305	3.25 - 6"	----	6 - 12"	10	42
3	TSG2030	1700	82 - 153	----	154 - 305	3.25 - 6"	----	6 - 12"	10	60
5	TSG2050	2300	100 - 178	----	179 - 305	4 - 7"	----	7 - 12"	10	174
10	TSG2100	3000	150 - 220	----	221 - 305	6 - 8.5"	----	8.5 - 12"	12	300
20	TSG2200	----	150 - 220	----	221 - 305	6 - 8.5"	----	8.5 - 12"	12	440