

V10 CLEVIS FOUNDRY HOOKS

The V10 Clevis Foundry Hook is made of premium quality, alloy steel and offers a unique feature - a wider throat to accommodate a variety of attachments. The clevis end permits quick and secure attachments to slings and chains. This Italian made foundry hook is approved for overhead lifting and is mainly used in a workshop or factory that produces metal castings. Quenched and tempered before proof testing, this Grade 100 foundry hook is of premium quality and will never let you down - just the load itself. It meets or exceeds OSHA, Government, NACM, and ASTM specs and comes in a blue powder coat finish.



FEATURES

- Grade 100
- Made from premium fine grain alloy steel
- Made in Italy
- Quenched and tempered before proof testing
- Blue powder coat finish
- Meets or exceeds OSHA, Government, NACM, and ASTM specs
- Suitable for foundry work



PRODUCT SPECIFICATIONS

Click on a product to view details or select multiple products to compare



Product	Manufacturer Part No.	Chain Size Inches	Chain Size mm	Dim A	Dim B	Dim C	Dim G	Dim H	Dim P x L	Dim R	Lbs. Per Ea.	Working Load Limit (Lbs.)
<input type="checkbox"/> 8787100	CYFX06	7/32	6	2.106	0.335	0.256	0.866	1.024	0.295 x 0.689	3.583	1.42	3100
<input type="checkbox"/> 8987200	CYFX07	9/32	7	2.520	0.394	0.453	1.024	1.220	0.354 x 0.886	4.740	2.40	4300
<input type="checkbox"/> 8987300	CYFX08	5/16	8	2.520	0.394	0.453	1.024	1.220	0.394 x 0.886	4.470	2.43	5700
<input type="checkbox"/> 8987400	CYFX10	3/8	10	2.992	0.512	0.591	1.181	1.339	0.512 x 1.240	5.157	3.84	8800
<input type="checkbox"/> 8987600	CYFX13	1/2	13	3.504	0.669	0.689	1.575	1.752	0.630 x 1.654	5.827	8.30	15000
<input type="checkbox"/> 8987700	CYFX16	5/8	16	3.976	0.748	0.846	1.772	1.988	0.827 x 2.028	7.815	12.68	22600

Compare

DESIGN

GRADE

- 100

FINISH

- Blue Powder Coat Finish

STANDARDS

- Meets or exceeds OSHA, Government, NACM, and ASTM specs

ATTACHMENT

- Clevis

HEAT TREATMENT

- Quenched and tempered before proof testing

ORIGIN

- Made in Italy

HOOK TYPE

- Foundry Hook

APPLICATION

- Overhead Lifting

MATERIAL

- Premium Fine Grain Alloy Steel