

PROLOK66™

ADJUSTABLE LEVER

LOADBINDER

The ProLok66™ comes with safety built in. It features a unique self-locking handle and easy-release thumb latch that is automatically engaged when the handle is closed. This locks the handle in the closed position until the load is released. This feature makes our adjustable binder safer than standard lever binders. The ProLok66™ adjusts to a full 2", giving the user optimum link location. No more problems getting that last extra half link hook-up.

Self-Locking Handle With Thumb Release

The handle safety latch is automatically engaged when the handle is closed. The handle remains locked as a safety precaution until the user engages the thumb release.

Easy-to-Use Adjustable Nut

The adjustable nut eliminates the need to remove and re-attach the binder hook on the chain in order to find the desirable location. The adjustable nut makes the ProLok66 quick and easy to use.

Full Two Inch Adjustment Range

Provides a full two inch adjustment range to provide optimum chain load tension.

Safety Pin Prevents Disconnection

As an added safety feature, the safety pin prevents the thread from disconnecting from the ProLok66.



PROLOK66™

ADJUSTABLE LEVER

LOADBINDER

FINISH

- High-visibility yellow powder coat paint

STANDARDS

- Meet all DOT/CVSA/CCMTA requirements

HOOKS

- Forged, yellow powder coat painted Grab Hooks

APPLICATION

- Cargo Control

TENSIONING MECHANISM

- Lever tensioning; built-in knurled adjustable nut

PROLOK66™ ADJUSTABLE LEVER LOADBINDER

PRODUCTS SPECIFICATIONS

Product	Chain Size (In.) - Grade 70	Take-Up (In.)	Handle Length (In.)	Quantity Per Pkg.	Lbs. Per Package	Working Load Limit (Lbs.)	Working Load Limit (kg)
H5025-0652	5/16 or 3/8	3.75	15.43	4	43	6600	2994