The Peerless® Standard Alloy Foundry Sorting Hook is ideally used for foundry and industrial sorting applications. This hook also comes in a standard size version.



FINISH

• Self-colored or blue-grey powder coat

STANDARDS

· Certified to OSHA and ASME standards

ATTACHMENT

Eye

ORIGIN

Made in USA

HOOK TYPE

• Foundry Sorting Hook - short version


APPLICATION

· Custom Lifting

MATERIAL

• 8620 or 4130 alloy Steel

DIAGRAM DRAWINGS



PRODUCTS SPECIFICATIONS

Product	Chain Size Inches	Dim A (in.)	Dim B (in.)	Dim C (in.)	Dim D (in.)	Dim E (in.)	Lbs. Per Ea.	Working Load Limit (Lbs.)
FSA050S	9/32	0.500	6.000	0.750	3.000	1.500	1.33	450
FSA063S	9/32	0.630	6.000	0.750	3.000	1.500	2.00	900
FSA075S	9/32	0.750	6.000	0.750	3.000	1.500	2.30	1400
FSA081S	3/8	0.810	6.000	0.880	3.000	1.500	2.88	2000
FSA100S	3/8	1.000	6.000	1.000	3.000	1.500	3.80	3000
FSA113S	3/8	1.130	6.000	1.000	3.000	1.500	4.70	4000
FSA125S	1/2	1.250	6.000	1.250	3.000	1.500	6.30	5500

