

GRADE 70 IMPORT TRANSPORT CHAIN (NACM)

Grade 70 was designed specifically to provide a light, yet strong chain for binding, tie-downs, towing, and construction use. Made from a variety of medium carbon and alloy materials. Induction heat treated, the chain meets all requirements set by the Department of Transportation (DOT), CCMTA & CVSA for truck tie-down use. Manufactured to ASTM 80 short link specs or NACM long link specs for reduced weight. Order unit is foot. NOT for overhead lifting.



GRADE 70 IMPORT TRANSPORT CHAIN (NACM)

GRADE

- 70

FINISH

- Yellow zinc

STANDARDS

- Meets all requirements set by the Department of Transportation (DOT), CCMTA & CVSA for truck tie-down use. Manufactured to ASTM 80 short link specs or NACM long link specs for reduced weight.

HEAT TREATMENT

- Induction heat treated

APPLICATION

- Load binding, tie-downs, towing, and logging operations

MATERIAL

- Medium carbon and alloy materials

GRADE 70 IMPORT TRANSPORT CHAIN (NACM)

PRODUCTS SPECIFICATIONS

Product	Package Type	Trade Size (in.)	Trade Size mm	Wire Dia. (in)	Inside Dim. Length (Nominal) (in.)	Inside Dim. Width (Min) (in.)	Ft. Per Package	Net Weight (Lbs.)	Working Load Limit (Lbs.)	Working Load Limit (kg)
H0317-0420	Full Drum	1/4	7	0.281	1.240	0.380	800	540	3150	1429
H0317-0520	Full Drum	5/16	8	0.343	1.290	0.440	550	586	4700	2132
H0317-0620	Full Drum	3/8	10	0.406	1.380	0.550	400	584	6600	2994
H0317-0820	Full Drum	1/2	13	0.531	1.790	0.720	200	500	11300	5127

