

QUIKBINDER PLUS™

A ratchet binder like no other.

The QuikBinder PLUS™ is a ratchet binder like nothing you've seen before. Its unique vinyl coated barrel on the free spin gear gives you a firm grip so you can take up as much slack on the chain as possible before ratcheting into final position. Quickly switch from extension, to take-up, or use the free spin mode for fast adjustment in either direction.

Its patented folding handle lets you quickly secure the load, and then tuck the handle out of the way from any potential snag. When the load is secure, be sure to use the QuikBinder Lock to ensure the safety of your cargo and protect against tampering.

3 Position Pawl With Three Gears

The QuikBinder Plus has an easy-to-use three position pawl which offers three gears. Ratchet extension, ratchet take-up, and free-spin mode for fast adjustment in either direction allowing you to take up extra slack in the chain very fast.

Patented Fold Down Handle

The fold down handle makes the QuikBinder safer and easy to use by eliminating any protrusions from the side of the truck.

Tamper-Proof locking mechanism with QuikBinder Lock

Have peace of mind knowing your load is secure during transportation or when left unattended.



QUIKBINDER PLUS™

FINISH

- High-visibility yellow powder coat paint

STANDARDS

- Federal Motor Carrier Safety Admin (FMCSA)
- Department of Transportation (DOT)
- Commercial Vehicle Safety Alliance (CVSA)
- SAE J684
- ANSI/ASAE S338.5

HOOKS

- Forged, yellow zinc plated grab hooks

APPLICATION

- Cargo Control

ACCESSORIES

- Tamper-proof QuikBinder Lock

TENSIONING MECHANISM

- Premium ratchet binder with vinyl coated barrel with 2 inches of adjustment on either end

QUIKBINDER PLUS™

PRODUCTS SPECIFICATIONS

| Product | Chain Size G70 or G80 (In.) | Take-Up (In.) | Folded Handle Length (in) | Straight Handle Length (in) | Quantity Per Pkg. | Lbs. Per Package | Working Load Limit (Lbs.) | Working Load Limit (kg) |
|------------|-----------------------------|---------------|---------------------------|-----------------------------|-------------------|------------------|---------------------------|-------------------------|
| H5125-0658 | 5/16 or 3/8 | 6 | 9.5 | 13.9 | 4 | 46 | 7100 | 3220 |
| H5125-0858 | 3/8 or 1/2 | 6 | 9.5 | 13.9 | 4 | 56 | 12000 | 5443 |
| H5125-0958 | 1/2 or 5/8 | 6 | 9.5 | 13.9 | 2 | 37 | 18100 | 8210 |

