

A316 STAINLESS STEEL QUICK LINKS

Whether you need a permanent or temporary connection, this low carbon A316 Stainless Steel Quick-Link will allow for a fast and easy attachment. This corrosive resistant link is available in different sizes to suit your needs with a Working Load Limit of up to 2,800 lbs. NOT for overhead lifting.



A316 STAINLESS STEEL QUICK LINKS

APPLICATION

- Various applications

MATERIAL

- A316 Stainless steel

A316 STAINLESS STEEL QUICK LINKS

PRODUCTS SPECIFICATIONS

Product	Trade Size (in.)	Dia. In.	Dia. (mm)	Inside Length (in)	Inside Width	Opening	Quantity Per Pkg.	Lbs. Per Ea.	Working Load Limit (Lbs.)	Working Load Limit (kg)
H8224-0240	1/8	0.125	3	1.300	0.390	0.200	5	0.04	220	100
H8224-0340	3/16	0.197	5	1.500	0.550	0.240	5	0.04	660	299
H8224-0440	1/4	0.240	6	1.780	0.550	0.280	5	0.07	880	399
H8224-0540	5/16	0.310	8	2.290	0.710	0.390	5	0.15	1760	798
H8224-0640	3/8	0.390	10	2.710	0.870	0.470	5	0.29	2200	998
H8224-0840	1/2	0.470	12	3.150	0.980	0.590	5	0.5	2600	1179