

DECK LASHING CHAIN

This heat treated, galvanized Deck Lashing Chain has a long link design and can be used with various attachments and fittings. Deck lashing chain is well suited for log lashing and securing cargo on container ships. Certified to Canadian Coast Guard TP2534E Code of Safe Practice for Ships Carrying Timber Deck Cargo and hallmark USA stamped on every link of chain. NOT for overhead lifting.



DECK LASHING CHAIN

FINISH

- Hot dip galvanized

HEAT TREATMENT

- Heat Treated

APPLICATION

- Marine Chain

STANDARDS

- Certified to Canadian Coast Guard TP2534E Code of Safe Practice for Ships Carrying Timber Deck Cargo
- Hallmarked USA on every link of chain and PCL every 6 links
- 4:1 Safety Factor

ORIGIN

- Made in USA

MATERIAL

- Steel

DECK LASHING CHAIN

PRODUCTS SPECIFICATIONS

Product	Finish	Trade Size (in.)	Wire Dia. (in)	Inside Dim. Length (Nominal) (in.)	Inside Dim. Width (Min) (in.)	Qty. Per Drum	Net Weight (Lbs.)	Working Load Limit (Lbs.)	Working Load Limit (kg)
8612312	HDG	1/2	0.531	0.930	3.150	1000	2182	9000	4080
560141301	HDG	1/2	0.531	3.150	0.930	460	1004	9000	4080

