



TCE

SPARK RESISTANT AIR HOIST

KITO[®]

No sparks, no worries.

You can rest easy knowing that the TCE-IIB spark resistant air hoist is built with components that will reduce or eliminate risk of spark produced by impact or friction in heavy-duty industrial applications. ATEX rated and Kito made - a perfect match.



- 1 Spark Resistant Load Chain**
The TCE IIB air hoist uses nickel plated chain for both spark and corrosion resistance.
- 2 Low Noise Levels**
Built for quiet operation for operator comfort, and therefore maximum productivity.
- 3 ATEX Certified Spark Resistant**
Rated II 2G Ex h IIB T4 Gb for gas and II 2D Ex h IIB 130C Db for dust and in compliance with the ATEX Directive 2014/34/EU.
- 4 Unlimited Duty Cycle**
The TCE is built for long and demanding work shifts with its unlimited duty cycle. The operator can continually operate the hoist without worrying about damage from too many strats per hour, allowing you to get the work done on your schedule.
- 5 Bronze Coated Hooks**
Spark resistant bronze coating on both top & bottom hooks.
- 6 Extremely Fast Lifting**
The 1/4 tonne model boasts an amazing 207 ft./min in the up direction with no load. Quickly reposition the hook in between loads to maximize your productivity.

All other specifications, dimensions, and drawings are available at www.kito.ca
Please call **1 888 322 KITO (5486)** for more information or assistance

WESTERN CANADA

309-3815 1ST AVE
BURNABY, BC
V5C 3V6

KITO®

EASTERN CANADA

4-3660 ODYSSEY DR
MISSISSAUGA, ON
L5M 0Y9

TCE SPARK RESISTANT AIR HOIST